

# OWIHP0530M-1R0

## SMD power inductor



### Description

Molded series with Alloy metal powder

### Features

High rated current  
 Frequency up to 3 MHz  
 125 deg. maximum total operation temperature  
 Low core loss  
 Ultra low buzz noise due to molding construction  
 Halogen Free & ROHS compliant

### Applications

Laptops and PCs  
 Switch and servers  
 Base stations  
 DC/DC converters  
 Battery powered devices  
 SSD modules

### General Specifications

Test Voltage	1.0V
Parameters Test Temp	20°C
Operation Temp	-55 to +125°C
(Including temperature Rise)	
Storage Temp	0 to 40°C
Storage Humidity	<70% RH
Resistance to Soldering Heat	260°C for 10 sec
Rated Current	L drops off 30% typ at Isat
Temperature Rise	40°C typ. at Irms

Inductance	Ltol.	Test freq.	DCR [mΩ]	Isat [A]	Irms [A]	Irated [mA]	Idc max [mA]	Q (min)	SRF[MHz]
1.00 uH	K, M, N	100 kHz	14.00	10.00	8,5				

When ordering, please specify tolerance code. Tolerance: K=±10%, M=±20%, N=±30%

## Shape and dimensions [mm]

A	B	C	D	E	F	G	H	I	J	Shape
5.40	5.20	2.80	1.2	2.2			2.5	1.9	2.2	
±0.35	±0.2	±0.2	Ref	Ref			Ref	Ref	Ref	



