

OWIHP0650M-2R2

SMD power inductor



Description

Molded series with Alloy metal powder

Features

High rated current
 Frequency up to 3 MHz
 125 deg. maximum total operation temperature
 Low core loss
 Ultra low buzz noise due to molding construction
 Halogen Free & ROHS compliant

Applications

Laptops and PCs
 Switch and servers
 Base stations
 DC/DC converters
 Battery powered devices
 SSD modules

General Specifications

Test Voltage	1.0V
Parameters Test Temp	20°C
Operation Temp	-55 to +125°C
(Including temperature Rise)	
Storage Temp	0 to 40°C
Storage Humidity	<70% RH
Resistance to Soldering Heat	260°C for 10 sec
Rated Current	L drops off 30% typ at Isat
Temperature Rise	40°C typ. at Irms

Inductance [μ H]	Ltol.	Test freq.	DCR [$m\Omega$]	Isat [A]	Irms [A]	Irated [mA]	Idc max [mA]	Q (min)	SRF[MHz]
2.20	K, M, N	100 kHz	12.50	11.00	9				

When ordering, please specify tolerance code. Tolerance: K=±10%, M=±20%, N=±30%

Shape and dimensions [mm]

A	B	C	D	E	F	G	H	I	J	Shape
7.00	6.60	3.80	1.6	3			3.5	2.35	3.7	
±0.3	±0.2	±0.2	Ref	Ref			Ref	Ref	Ref	

