

# OWIDNR252012-R24

## SMD Power inductor



### Description

Half-shielded magnetic epoxy core

### Features

RoHS, Halogen Free and REACH Compliance  
 Shielded and miniature design  
 Shielded power inductor  
 Side soldering process

### Applications

Smartphones, tablets and wearable devices DSC, camcorders DC/DC converters etc.

### General Specifications


Test Voltage	0.1V
Parameters Test Temp	25°C
Operation Temp (Including temperature Rise)	-40 to +125°C
Storage Temp	0 to 40°C
Storage Humidity	<70% RH
Resistance to Soldering Heat	260°C for 10 sec
Rated Current	<b>L drops off 30% typ at Isat</b>
Temperature Rise	40°C typ. at Irms

Inductance	Ltol.	Test freq.	DCR [mΩ]	Isat [A]	Irms [A]	Irated [mA]	Idc max [mA]	Q (min)	SRF[MHz]
0.24 uH	M, P, N	1MHz	32.00	4.05	3,5				

When ordering please specify tolerance code Tolerance: M=±20%, P=±25%, N=±30%

### Shape and dimensions [mm]

A	B	C	D	E	F	G	H	I	J	Shape
2.00	2.50	1.25	0.8	2.6			2.6	1.2	0.7	
+0.35 -0.1	+0.3 -0.1	Max	Ref	Ref			Ref	Ref	Ref	



Magnetic shielding

