

# OWIRH8D43-1R0

## SMD Power inductor



### Description

Metal base 2pcs, Hexagon Type

### Features

RoHS, Halogen Free and REACH Compliance  
 Shielded power inductor  
 Various package sizes  
 Wide inductance range

### Applications

Power supply for VTR, OA equipment  
 LCD television, notebook PC  
 Portable communication equipment  
 DC/DC converters, etc.

### General Specifications

Test Voltage	0.25V
Parameters Test Temp	25°C
Operation Temp (Including temperature Rise)	-40°C to +125°C
Storage Temp	0~40°C
Storage Humidity	<70% RH
Resistance to Soldering Heat	260°C for 10 sec
Rated Current	L drops off 35% typ at Isat
Temperature Rise	

Inductance [ $\mu$ H]	Ltol.	Test freq.	DCR [ $m\Omega$ ]	Isat [A]	I <sub>rms</sub> [A]	I <sub>rated</sub> [mA]	I <sub>dc max</sub> [mA]	Q (min)	SRF[MHz]
1.00	M, P, N	100 kHz	10.50	8.20					

When ordering please specify tolerance code Tolerance: M=±20%, P=±25%, N=±30%

## Shape and dimensions [mm]

A	B	C	D	E	F	G	H	I	J	Shape
8.30	10.80	4.50	1.2	6.3	2.5		2.8	2	6.1	
Max	Max	Max	Ref	Ref	Ref		Ref	Ref	Ref	

