

OWI0520LC-220

SMD Power inductor



Description

SMD Power inductor

Features

RoHS, Halogen Free and REACH Compliance

Applications

Power supply for VTR, OA equipment
 LCD television set, notebook PC
 Portable communication equipment
 DC/DC converters, etc.

General Specifications

Test Voltage	0.25V
Parameters Test Temp	25°C
Operation Temp (Including temperature Rise)	-40°C to +125°C
Storage Temp	0 to 40°C
Storage Humidity	<70% RH
Resistance to Soldering Heat	260°C for 10 sec
Rated Current	L drops off 35% typ at Isat
Temperature Rise	40°C typ. at Irms

Inductance	Ltol.	Test freq.	DCR [mΩ]	Isat [A]	Irms [A]	Irated [mA]	Idc max [mA]	Q (min)	SRF[MHz]
22.00 uH	M, P, N	100 kHz	320.00	0.56	0,6				

When ordering please specify tolerance code Tolerance: M=±20%,P=±25%,N=±30%

Shape and dimensions [mm]

A	B	C	D	E	F	G	H	I	J	Shape
5.00	5.00	2.20	4.1	1.75	0.66		2.2	1.5	3.8	Fig.1
±0.3	±0.3	Max	Ref	Ref	Ref		Ref	Ref	Ref	

Fig.1




Fig.2




Fig.1




Fig.2

