

OWI0630CB-1R5

SMD Power inductor



Description

SMD Power inductor

Features

RoHS, Halogen Free and REACH Compliance
Magnetically shielded and low DC resistance
Suitable for large currents.
Available on tape reel for auto-insertion
Ideal for a variety of DC-DC converter applications.

Applications

Power supply for VTR, OA equipment
LCD television set, notebook PC
Portable communication equipment
DC/DC converters, etc.

General Specifications

Test Voltage	0.25V
Parameters Test Temp	25°C
Operation Temp (Including temperature Rise)	-40°C to +125°C
Storage Temp	0 to 40°C
Storage Humidity	<70% RH
Resistance to Soldering Heat	260°C for 10 sec
Rated Current	L drops off 35% typ at Isat
Temperature Rise	

Inductance [μ H]	Ltol.	Test freq.	DCR [$m\Omega$]	Isat [A]	I _{rms} [A]	I _{rated} [mA]	I _{dc max} [mA]	Q (min)	SRF[MHz]
1.50	M, P, N	100 kHz	17.60	2.93	3,68				

When ordering please specify tolerance code Tolerance: M=±20%, P=±25%, N=±30%

Shape and dimensions [mm]

A	B	C	D	E	F	G	H	I	J	Shape
6.30	6.30	3.10	2				2.4	1.45	4.3	Fig.1
Max	Max	Max	Ref				Ref	Ref	Ref	

